

高度 (B)	长度 (A)	厚度		连接管口 间距 C	托架长度	尺寸 D	托架间距 E	散热量(W)		散热量(W)		含盖版的重量 (kg)		水容量 (L)			
		22型	33型					95/70/18℃		80/60/20℃		22型	33型	22型	33型	22型	33型
								22型	33型	22型	33型						
300	800	105	160	245	177	137.5	525	1188	1702	891	1207	13.92	20.88	2.72	4.08		
	1000	105	160	245	177	137.5	725	1485	2128	1114	1509	17.40	26.10	3.40	5.10		
	1200	105	160	245	177	137.5	925	1782	2554	1337	1811	20.88	31.32	4.08	6.12		
	1400	105	160	245	177	137.5	1125	2079	2979	1559	2113	24.36	36.54	4.76	7.14		
	1600	105	160	245	177	137.5	1325	2376	3405	1782	2414	27.84	41.76	5.44	8.16		
	1800	105	160	245	177	137.5	1525	2673	3830	2005	2716	31.32	46.98	6.12	9.18		
	2000	105	160	245	177	137.5	1725	2970	4256	2228	3018	34.80	52.20	6.80	10.20		
	2200	105	160	245	177	137.5	1925	3267	4681	2450	3320	38.28	57.42	7.48	11.22		
400	800	105	160	345	177	137.5	525	1488	2124	1116	1506	18.56	28.48	3.20	4.80		
	1000	105	160	345	177	137.5	725	1860	2655	1395	1883	23.20	35.60	4.00	6.00		
	1200	105	160	345	177	137.5	925	2232	3186	1674	2259	27.84	42.72	4.80	7.20		
	1400	105	160	345	177	137.5	1125	2604	3717	1953	2636	32.48	49.84	5.60	8.40		
	1600	105	160	345	177	137.5	1325	2976	4248	2232	3013	37.12	56.96	6.40	9.60		
	1800	105	160	345	177	137.5	1525	3348	4779	2511	3389	41.76	64.08	7.20	10.80		
	2000	105	160	345	177	137.5	1725	3720	5310	2790	3766	46.40	71.20	8.00	12.00		
	2200	105	160	345	177	137.5	1925	4092	5841	3069	4142	51.04	78.32	8.80	13.20		
500	800	105	160	445	277	137.5	525	1772	2516	1329	1784	23.28	35.20	3.84	5.76		
	1000	105	160	445	277	137.5	725	2215	3145	1661	2230	29.10	44.00	4.80	7.20		
	1200	105	160	445	277	137.5	925	2658	3774	1994	2676	34.92	52.80	5.76	8.64		
	1400	105	160	445	277	137.5	1125	3101	4403	2326	3122	40.74	61.60	6.72	10.08		
	1600	105	160	445	277	137.5	1325	3544	5032	2658	3568	46.56	70.40	7.68	11.52		
	1800	105	160	445	277	137.5	1525	3987	5661	2990	4014	52.38	79.20	8.64	12.96		
600	400	105	160	545	377	137.5	125	1021	1444	766	1024	13.48	20.48	2.24	3.36		
	600	105	160	545	377	137.5	325	1532	2166	1149	1536	20.22	30.72	3.36	5.04		
	800	105	160	545	377	137.5	525	2042	2888	1532	2048	26.96	40.96	4.48	6.72		
	1000	105	160	545	377	137.5	725	2553	3610	1915	2560	33.70	51.20	5.60	8.40		
	1200	105	160	545	377	137.5	925	3064	4332	2298	3072	40.44	61.44	6.72	10.08		
	1400	105	160	545	377	137.5	1125	3574	5054	2681	3584	47.18	71.68	7.84	11.76		
	1600	105	160	545	377	137.5	1325	4085	5776	3064	4096	53.92	81.92	8.96	13.44		
	1800	105	160	545	377	137.5	1525	4595	6498	3447	4608	60.66	92.16	10.08	15.12		
	2000	105	160	545	377	137.5	1725	5106	7220	3830	5120	67.40	102.40	11.20	16.80		
	2200	105	160	545	377	137.5	1925	5617	7942	4213	5632	74.14	112.64	12.32	18.48		
2400	105	160	545	377	137.5	2125	6127	8664	4596	6144	80.88	122.88	13.44	20.16			
900	400	105	160	845	677	137.5	125	1393	1946	1046	1380	20.88	30.48	3.20	4.80		
	600	105	160	845	677	137.5	325	2090	2919	1569	2070	31.32	45.72	4.80	7.20		
	800	105	160	845	677	137.5	525	2786	3892	2092	2760	41.76	60.96	6.40	9.60		
	1000	105	160	845	677	137.5	725	3483	4865	2615	3450	52.20	76.20	8.00	12.00		
	1200	105	160	845	677	137.5	925	4179	5838	3138	4140	62.64	91.44	9.60	14.40		